SFL1-45





SMART Flood Light 45W

Rating: Not Rated Yet
Ask a question about this product

Description









SPECIFICATION

	SFL1-160	SFL1-90	SFL1-60	SFL1-45
LED Quantity	132pcs	72pos	48pcs	36pcs
Rated Power	162W(white colour)/135W(RGB)	88W(white colour)/76W(RGB)	60W(white colour)/52W(RGB)	45W(white colour)46W(RGB)
Input Voltage	AC100-240V	AC100-240V	AC100-240V	AC100-240V
Frequency Range	SGISCHIZ	SOISOHZ	50/60Hz	50/60Hz
Power Factor	>0.9	>0.9	>0.9	>0.9
THD	<15%	<15%	<15%	<15%
Colour Choose	White/RGB(44R+44G+44B)	White/RGB(24R+24G+24B)	White/RGB(16R+16G+16B)	White/RGB(12R+12G+12B)
White Colour Temperature	6500K/4500K/3200K	6500K/4500K/3200K	6500K/4500K/3200K	6500K/4500K/3200K
Colour Rendering Index	>70/6500K	>70/6500K	>70/6500K	>70/6500K
Lamp Luminous Flus(Lm)	10526lm(white)/5380lm(RGB)	5835lm(white)/2981lm(RGB)	3874lm(white)/1980lm(RGB)	3085lm(white)/1577lm(RGE
Beam Angle Choose	10"/25"/40"/60"	101/251/401/601	101/251/401/501	101/251/401/601
Control Mode	Constant current/DMX512	Constant ourrent/DMX512	Constant current/DMX512	Constant current/DMX512
Temp.of Working Condition	-25°C to 50°C	-25°C to 50°C	-25°C to 50°C	-25°C to 50°C
Hud. Of Working Condition	10% to 90%	10% to 90%	10% to 90%	10% to 90%
Lifespan	>50 000 Hours	>50 000 Hours	>50 000 Hours	>50 000 Hours
Warranty	3 years	3 years	3 years	3 years
Protection Grade	IP65	IP65	IP65	IP65
IK Grade	IK10	IK10	IK10	IK10
Installation Hole Distance	Ф12 x 100mm	Ф12 x 100mm	Ф12 x 100mm	Ф12 x 100mm
Larrp Weight (Kg)	16	10	7	7
Carton Packing Size	57cm x 21cm x 65cm	45cm x 20cm x 54cm	36cm x 17cm x 48cm	36cm x 17cm x 48cm
Gross Weight (Kg)	18	12	8	8
Certificate	CE /Rohs	CE /Rohs	CE /Rohs	CE /Rohs