

SLB2-1



SMART LED Bulb 1W

Rating: Not Rated Yet
[Ask a question about this product](#)

Description

	SLB2-1	SLB2-2	SLB2-3A	SLB2-3B
				
Rated Power	1 W	2 W	3 W	3 W
LED Type	SMD3528	SMD3528	SMD3528	SMD3530
Casing	Plastic Cover with air heat ventilation holes	Plastic Cover with air heat ventilation holes	Plastic Cover with air heat ventilation holes	Plastic Cover with air heat ventilation holes
Input Voltage	90-260 VAC or 12 VDC 10.5-14.5V) or 24 VDC (21-29V)	90-260 VAC or 12 VDC 10.5-14.5V) or 24 VDC (21-29V)	90-260 VAC or 12 VDC 10.5-14.5V) or 24 VDC (21-29V)	90-260 VAC or 12 VDC 10.5-14.5V) or 24 VDC (21-29V)
Colour Temperature(Kelvin)	6000K : Cool White 4000K : White 2700K : Warm White	6000K : Cool White 4000K : White 2700K : Warm White	6000K : Cool White 4000K : White 2700K : Warm White	6000K : Cool White 4000K : White 2700K : Warm White
Lamp Luminous Flux(Lm)	80lm	160lm	220lm	220lm
Temperature of Working Condition	-25°to 50°	-20°to 40°	-20°to 40°	-20°to 40°
Lifespan	>50,000 Hours	>50,000 Hours	>50,000 Hours	>50,000 Hours
Fitting	E12, E14, E26, E27, B22	E12, E14, E26, E27, B22	E12, E14, E26, E27, B22	E12, E14, E26, E27, B22
Warranty	2 years	2 years	2 years	2 years
Weight (g)	85	105	115	235
Size (mm)	Φ 50 mm Height : 105 mm	Φ 50 mm Height : 105 mm	Φ 50 mm Height : 105 mm	Φ 60 mm Height : 135 mm
Certificate	CE/Rohs	CE/Rohs	CE/Rohs	CE/Rohs