

EPIPDB-COM-20A



Dual Battery Series 20A, 12/24V AUTO

Rating: Not Rated Yet
[Ask a question about this product](#)

Description

Recommended Application

- RVs, Caravans, bus, boats
- Long distance surveillance. With remote meter MT-1 and MT-2 optional.

Features

- Charge two battery banks. No load terminals
- Two battery charging eliminates the extra cost of two separate solar charging system
- Intelligent System Optimum Control
- 12/24V auto work
- Battery type selection
- Charging frequency optional
- High efficient Series PWM charging
- Local external temperature compensation
- Remote temperature sensor optional
- Use MOSFET as electronic switch, without any mechanical switch
- Remote meter MT-1 and MT-2 optional
- Load and battery status indicators
- Electronic protection, over charging, short circuit, battery reverse polarity protection

	EPIPDB-COM, 10A, 12/24V	EPIPDB-COM, 20A, 12/24V
Rated Current	10 A	20 A
Max PV Voc	12/24V AUTO	12/24V AUTO
Dimension	140x65x34mm	144x73x45mm
Mounting Dimension	120x45mm	126x55mm
Mounting Hole	Φ4.5	Φ4.5
Terminals	4 mm ²	4 mm ²
Net Weight	0.15kg	0.25kg
Working Temperature	-35°C to +55°C	-35°C to +55°C

	EPIPDC-COM, 10A, 12/24V	EPIPDC-COM, 20A, 12/24V
Rated Current	10 A	20 A
Max PV Voc	12/24V AUTO	12/24V AUTO
Options	• Battery type selection through MT-2	• Battery type selection through MT-2
Dimension	140x65x34mm	144x73x45mm
Mounting Dimension	130x45mm	135x55mm
Mounting Hole	Φ4.5	Φ4.5
Terminals	4 mm ²	4 mm ²
Net Weight	0.15kg	0.25kg