

SS-1024R




Sea Star Series 10A, 24V

Rating: Not Rated Yet
[Ask a question about this product](#)

Description

- Recommended Application**
- Solar home system, solar traffic system, solar CCTV system , and wild automatic detection device etc.
 - Public lighting area, such as solar street light, garden light, billboard, insect light, and wild automatic detection device
 - Ideal for humid area, such as marine application
- Features**
- Use MOSFET as electronic switch, without any mechanical switch
 - Gel, Sealed and Flooded battery type option
 - Electronic protection: Overheating, over charging, over discharging, overload, and short circuit
 - Reverse polarity protection: Any combination of solar module and battery

	SS-1024	SS-1524	SS-2024
			
Rated Current	10 A	15 A	20 A
Max PV Voc	120V AUTO	120V AUTO	120V AUTO
Features	<ul style="list-style-type: none">ManualON/OFFAluminum caseMoistureproof	<ul style="list-style-type: none">ManualON/OFFAluminum caseMoistureproof	<ul style="list-style-type: none">ManualON/OFFAluminum caseMoistureproof
Dimension	132x70 x50mm	137x86x46mm	137x86x46mm
Mounting Dimension	122x40mm	127x50mm	127x50mm
Mounting Hole	Ø4.5	Ø4.5	Ø4.5
Terminal	6 mm ²	10 mm ²	10 mm ²
Net Weight	0.15kg	0.25kg	0.25kg
Working Temperature	-35°C to +55°C	-35°C to +55°C	-35°C to +55°C

	SS-1024R	SS-1524R	SS-2024R
			
Rated Current	10 A	15 A	20 A
Max PV Voc	120V AUTO	120V AUTO	120V AUTO
Features	<ul style="list-style-type: none">Aluminum caseMoistureproofLoad work mode: Dark to Dawn, Light On+qualifier, Test, ON/OFFIntelligent timer function with 1-15 hours optionUnique dual timer function, enhance the flexibility of street light system	<ul style="list-style-type: none">Aluminum caseMoistureproofLoad work mode: Dark to Dawn, Light On+qualifier, Test, ON/OFFIntelligent timer function with 1-15 hours optionUnique dual timer function, enhance the flexibility of street light system	<ul style="list-style-type: none">Aluminum caseMoistureproofLoad work mode: Dark to Dawn, Light On+qualifier, Test, ON/OFFIntelligent timer function with 1-15 hours optionUnique dual timer function, enhance the flexibility of street light system
Dimension	132x70 x50mm	137x86x46mm	137x86x46mm
Mounting Dimension	122x40mm	127x50mm	127x50mm
Mounting Hole	Ø4.5	Ø4.5	Ø4.5
Terminal	6 mm ²	10 mm ²	10 mm ²
Net Weight	0.15kg	0.25kg	0.25kg
Working Temperature	-35°C to +55°C	-35°C to +55°C	-35°C to +55°C