

SS-1524



Sea Star Series 15A, 24V

Rating: Not Rated Yet
[Ask a question about this product](#)

Description

- Recommended Application**
- Solar home system, solar traffic system, solar CCTV system , and wild automatic detection device etc.
 - Public lighting area, such as solar street light, garden light, billboard, insect light, and wild automatic detection device
 - Ideal for humid area, such as marine application
- Features**
- Use MOSFET as electronic switch, without any mechanical switch
 - Gel, Sealed and Flooded battery type option
 - Electronic protection: Overheating, over charging, over discharging, overload, and short circuit
 - Reverse polarity protection: Any combination of solar module and battery

	SS-1024	SS-1524	SS-2024
			
Rated Current	10 A	15 A	20 A
Max PV Voc	120KV AUTO	120KV AUTO	120KV AUTO
Features	• ManualON/OFF • Aluminum case • Moistureproof	• ManualON/OFF • Aluminum case • Moistureproof	• ManualON/OFF • Aluminum case • Moistureproof
Dimension	120x70.5x30mm	137x89x48mm	137x89x48mm
Mounting Dimension	122x40mm	127x50mm	127x50mm
Mounting Hole	Ø4.5	Ø4.5	Ø4.5
Terminal	6 mm ²	10 mm ²	10 mm ²
Net Weight	0.15kg	0.25kg	0.25kg
Working Temperature	-35℃ to +65℃	-35℃ to +65℃	-35℃ to +65℃

	SS-1024R	SS-1524R	SS-2024R
			
Rated Current	10 A	15 A	20 A
Max PV Voc	120KV AUTO	120KV AUTO	120KV AUTO
Features	• Aluminum case • Moistureproof • Load work mode: Dark to Dawn, Light On/Off timer, Test, ON/OFF • Intelligent timer function with 1-15 hours option • Unique dual timer function, enhance the flexibility of street light system	• Aluminum case • Moistureproof • Load work mode: Dark to Dawn, Light On/Off timer, Test, ON/OFF • Intelligent timer function with 1-15 hours option • Unique dual timer function, enhance the flexibility of street light system	• Aluminum case • Moistureproof • Load work mode: Dark to Dawn, Light On/Off timer, Test, ON/OFF • Intelligent timer function with 1-15 hours option • Unique dual timer function, enhance the flexibility of street light system
Dimension	120x70.5x30mm	137x89x48mm	137x89x48mm
Mounting Dimension	122x40mm	127x50mm	127x50mm
Mounting Hole	Ø4.5	Ø4.5	Ø4.5
Terminal	6 mm ²	10 mm ²	10 mm ²
Net Weight	0.15kg	0.25kg	0.25kg
Working Temperature	-35℃ to +65℃	-35℃ to +65℃	-35℃ to +65℃