

SS-1524R



Sea Star Series 15A, 24V

Rating: Not Rated Yet
[Ask a question about this product](#)

Description

Recommended Application - Solar home system, solar traffic system, solar CCTV system , and wild automatic detection device etc. - Public lighting area, such as solar street light, garden light, billboard, insect light, and wild automatic detection device - Ideal for humid area, such as marine application			
Features - Use MOSFET as electronic switch, without any mechanical switch - Gel Sealed and Flooded battery type option - Electronic protection: Overheating, over charging, over discharging, overload, and short circuit - Reverse polarity protection: Any combination of solar module and battery			
			
Rated Current	10 A	15 A	20 A
Max PV Voc	120kV AUTO	120kV AUTO	120kV AUTO
Features	- Manual ON/OFF - Aluminum case - Moistureproof	- Manual ON/OFF - Aluminum case - Moistureproof	- Manual ON/OFF - Aluminum case - Moistureproof
Dimension	132x70.5x30mm	137x85x48mm	137x85x48mm
Mounting Dimension	122x40mm	127x50mm	127x50mm
Mounting Hole	Ø4.5	Ø4.5	Ø4.5
Terminals	6 mm²	10 mm²	10 mm²
Net Weight	0.18kg	0.28kg	0.28kg
Working Temperature	-35℃ to +55℃	-35℃ to +55℃	-35℃ to +55℃

			
Rated Current	10 A	15 A	20 A
Max PV Voc	120kV AUTO	120kV AUTO	120kV AUTO
Features	- Aluminum case - Moistureproof - Load work mode: Dark to Dawn, Light On-duttimer, Test, ON/OFF - Intelligent timer function with 1-15 hours option - Unique dual timer function, enhance the flexibility of street light system	- Aluminum case - Moistureproof - Load work mode: Dark to Dawn, Light On-duttimer, Test, ON/OFF - Intelligent timer function with 1-15 hours option - Unique dual timer function, enhance the flexibility of street light system	- Aluminum case - Moistureproof - Load work mode: Dark to Dawn, Light On-duttimer, Test, ON/OFF - Intelligent timer function with 1-15 hours option - Unique dual timer function, enhance the flexibility of street light system
Dimension	132x70.5x30mm	137x85x48mm	137x85x48mm
Mounting Dimension	122x40mm	127x50mm	127x50mm
Mounting Hole	Ø4.5	Ø4.5	Ø4.5
Terminals	6 mm²	10 mm²	10 mm²
Net Weight	0.18kg	0.28kg	0.28kg
Working Temperature	-35℃ to +55℃	-35℃ to +55℃	-35℃ to +55℃