SS-2024

Sea Star Series 20A, 24V

Rating: Not Rated Yet
Ask a question about this product

Description

Recommended Application

- Solar home system, solar traffic system, solar CCTV system , and wild automatic detection device etc.
- Public lighting area, such as solar street light, garden light, billboard, insect light, and wild automatic detection device
- Ideal for humid area, such as marine application

Features

- Use MOSFET as electronic switch, without any mechanical switch
- Gel, Sealed and Flooded battery type option
- Electronic protection: Overheating, over charging, over discharging, overload, and short circuit
- Reverse polarity protection: Any combination of solar module and battery

	SS-1024	SS-1524	SS-2024
Rated Current	10 A	15 A	20 A
Max PV Voc	12/24V AUTO	12/24V AUTO	12/24V AUTO
Features	• ManualON/OFF • Aluminum case • Moistureproof	• ManualON/OFF • Aluminum case • Moistureproof	• ManualON/OFF • Aluminum case • Moistureproof
Dimension	132x70.5x30mm	137x86x48mm	137x86x48mm
Mounting Dimension	122x40mm	127x50mm	127x50mm
Mounting Hole	Φ4.5	Φ4.5	Φ4.5
Terminals	6 mm²	10 mm²	10 mm²
Net Weight	0.19kg	0.25kg	0.25kg
Working Temperature	-35℃ to +55℃	-35℃ to +55℃	-35℃ to +55℃

	SS-1024R	SS-1524R	SS-2024R
Rated Current	10 A	15 A	20 A
Max PV Voc	12/24V AUTO	12/24V AUTO	12/24V AUTO
Features	• Aluminum case • Moistureproof • Load work mode: Dusk to Dawn, Light On+dualtimer, Test, ON/OFF • Intelligent timer function with 1-15 hours option • Unique dual timer function, enhance the flexibility of street light system	• Aluminum case • Moistureproof • Load work mode: Dusk to Dawn, Light On+dualtimer, Test, ON/OFF • Intelligent timer function with 1-15 hours option • Unique dual timer function, enhance the flexibility of street light system	• Aluminum case • Moistureproof • Load work mode: Dusk to Dawn, Light On+dualtimer, Test, ON/OFF • Intelligent timer function with 1-15 hours option • Unique dual timer function, enhance the flexibility of street light system
Dimension	132x70.5x30mm	137x86x48mm	137x86x48mm
Mounting Dimension	122x40mm	127x50mm	127x50mm
Mounting Hole	Φ4.5	Φ4.5	Φ4.5
Terminals	6 mm²	10 mm²	10 mm²
Net Weight	0.19kg	0.25kg	0.25kg
Working Temperature	-35℃ to +55℃	-35℃ to +55℃	-35℃ to +55℃