

SS-2024R



Sea Star Series 20A, 24V

Rating: Not Rated Yet
[Ask a question about this product](#)

Description

Recommended Application

- Solar home system, solar traffic system, solar CCTV system , and wild automatic detection device etc.
- Public lighting area, such as solar street light, garden light, billboard, insect light, and wild automatic detection device
- Ideal for humid area, such as marine application

Features

- Use MOSFET as electronic switch, without any mechanical switch
- Get Sealed and Flooded battery type option
- Electronic protection: Overheating, over charging, over discharging, overload, and short circuit
- Reverse polarity protection: Any combination of solar module and battery

	SS-1024	SS-1524	SS-2024
Rated Current	10 A	15 A	20 A
Max PV Voc	120V AUTO	120V AUTO	120V AUTO
Features	<ul style="list-style-type: none"> Manual ON/OFF Aluminum case Moistureproof 	<ul style="list-style-type: none"> Manual ON/OFF Aluminum case Moistureproof 	<ul style="list-style-type: none"> Manual ON/OFF Aluminum case Moistureproof
Dimension	132x70 5x30mm	137x85x48mm	137x85x48mm
Mounting Dimension	122x40mm	127x50mm	127x50mm
Mounting Hole	Ø4.5	Ø4.5	Ø4.5
Terminals	6 mm ²	10 mm ²	10 mm ²
Net Weight	0.18kg	0.25kg	0.28kg
Working Temperature	-35°C to +55°C	-35°C to +55°C	-35°C to +55°C

	SS-1024R	SS-1524R	SS-2024R
Rated Current	10 A	15 A	20 A
Max PV Voc	120V AUTO	120V AUTO	120V AUTO
Features	<ul style="list-style-type: none"> Aluminum case Moistureproof Load work mode: Dusk to Dawn, Light On+subtimer, Text, ON/OFF Intelligent timer function with 1-15 hours option Unique dual timer function, enhance the flexibility of street light system 	<ul style="list-style-type: none"> Aluminum case Moistureproof Load work mode: Dusk to Dawn, Light On+subtimer, Text, ON/OFF Intelligent timer function with 1-15 hours option Unique dual timer function, enhance the flexibility of street light system 	<ul style="list-style-type: none"> Aluminum case Moistureproof Load work mode: Dusk to Dawn, Light On+subtimer, Text, ON/OFF Intelligent timer function with 1-15 hours option Unique dual timer function, enhance the flexibility of street light system
Dimension	132x70 5x30mm	137x85x48mm	137x85x48mm
Mounting Dimension	122x40mm	127x50mm	127x50mm
Mounting Hole	Ø4.5	Ø4.5	Ø4.5
Terminals	6 mm ²	10 mm ²	10 mm ²
Net Weight	0.18kg	0.25kg	0.28kg
Working Temperature	-35°C to +55°C	-35°C to +55°C	-35°C to +55°C