

Tracer-1210






Tracer Series 10A, 100V

Rating: Not Rated Yet
[Ask a question about this product](#)

Description

- Recommended Application**
- Public lighting area, such as solar street light, garden light, billboard, intersection light, and wild automatic detection device
 - Ideal for solar lighting system with two lamps that needs different timer setting

- Features**
- MPPT solar controller
 - Battery option: Sealed, Flood and Gel
 - RJ45 interface with remote meter MT-2
 - CE, ISO9001:2008
 - Tracking efficiency: 99%
 - Conversion efficiency: 97%
 - Widely used, automatic recognize day/night
 - Timer function with 1-15 hours option for street light
 - Temperature compensation
 - Dual load output
 - Electronic protection: Over charging, over discharging, overload, short circuit, and reverse polarity of battery

	Tracer-1206	Tracer-1210	Tracer-1215
			
Rated Current	10 A	10 A	15 A
Max PV Voc	60 V	100 V	150 V
Rated Voltage	12V/24V AUTO	12V/24V AUTO	12V/24V AUTO
Rated Input Power	12V System :120W 24V System : 240W	12V System :120W 24V System : 240W	12V System :120W 24V System : 240W
Dimension	100x74x7mm	150x74x7mm	150x74x7mm
Mounting Dimension	150x70mm	150x70mm	150x70mm
Mounting Hole	Ø4.5	Ø4.5	Ø4.5
Terminals	4 mm ²	4 mm ²	4 mm ²
Net Weight	0.45kg	0.45kg	0.45kg
Working Temperature	-35°C to +55°C	-35°C to +55°C	-35°C to +55°C