

SSL1-60



Street Light 60W

Rating: Not Rated Yet
[Ask a question about this product](#)

Description

ADVANCED FEATURES

- Superior Heat-removal Capability.** According to the conduction, radicalization and convection heat removal design, when the temperature is 35°C, the LED junction temperature is less than 75°C.
- Scientific Photic Design.** Unique design of the lamp body, completely fit for the road lighting standard and with unique design of Lens plus Reflector technology. The efficiency of light luminous Flux is more than 95%.
- High Efficiency Power Driver.** Power driver efficiency is more than 90%, power factor is more than 0.99. It makes the light more stable and the lifespan is more longer (At least 50,000 hours).
- Power Driver Heat-removal Design.** The best heat-removal system of power driver, it could control the working temperature of the power driver and make it more stable in working.
- Multi-angle Installation Design.** Adjustable angle from -12° to 30° install on horizontal pole. Adjustable angle from 0° to 42° install on vertical pole.
- External Wiring Connection Box Design.** Unique design of the external connection box, it makes connection wire out of the connection box, make us to operate easily and more waterproof.
- Double bushing Design.** Can be fit for many pipes of different diameters in installation.

SPECIFICATION

	SSL1-30	SSL1-60	SSL1-90	SSL1-120	SSL1-160
Power	30watts	60watts	90watts	120watts	160watts
LED Qty	144pcs	288pcs	432pcs	576pcs	768pcs
Input voltage	AC100v ~ AC277V or DC12V/DC24V	AC100v ~ AC277V or DC12V/DC24V	AC100v ~ AC277V or DC12V/DC24V	AC100v ~ AC277V	AC100v ~ AC277V
Frequency Range	50~60Hz	50~60Hz	50~60Hz	50~60Hz	50~60Hz
Power Factor	>0.95	>0.95	>0.95	>0.95	>0.95
Total Power Consumption	32Wwatts	67Wwatts	103Wwatts	134Wwatts	173Wwatts
LED Power	28Wwatts	56Wwatts	81Wwatts	121Wwatts	161Wwatts
Colour Temperature	5000k ~ 7000k	5000k ~ 7000k	5000k ~ 7000k	5000k ~ 7000k	5000k ~ 7000k
Emission Colour	Cool White	Cool White	Cool White	Cool White	Cool White
Colour Rendering Index	>70	>70	>70	>70	>70
Lamp Luminous Flux	2405 lm	5180 lm	7788 lm	10848 lm	13740 lm
Lamp Efficiency	>80%	>80%	>80%	>80%	>80%
Efficiency of Light Luminous Flux	>95%	>95%	>95%	>95%	>95%
Temperature of Working Condition	-25°C-50°C	-25°C-50°C	-25°C-50°C	-25°C-50°C	-25°C-50°C
Humidity of Working condition	10% ~ 90%	10% ~ 90%	10% ~ 90%	10% ~ 90%	10% ~ 90%
Lifespan	> 50,000 Hours	> 50,000 Hours	> 50,000 Hours	> 50,000 Hours	> 50,000 Hours
Warranty period	3 Years	3 Years	3 Years	3 Years	3 Years
Protection Grade	IP65	IP65	IP65	IP65	IP65
Installation Pipe Diameter	Φ48mm-Φ60mm	Φ48mm-Φ60mm	Φ76mm-Φ60mm	Φ76mm-Φ60mm	Φ76mm-Φ60mm
Advice Installation Height	5-6M	5-7M	8-9M	9-10M	11-12M
Net Weight	4.6Kg	9Kg	14.3 Kg	14.6 Kg	17 Kg
Packing Size	62cmx32cmx18cm	79cmx35cmx18cm	93cmx42cmx18cm	93cmx42cmx18cm	100cmx42cmx18cm
Certificate	CES RoHS/ISO9001/UL	CES RoHS/ISO9001/UL	CES RoHS/ISO9001/UL	CES RoHS/ISO9001/UL	CES RoHS/ISO9001/UL