

SSL2-60



Street Light 60W

Rating: Not Rated Yet
[Ask a question about this product](#)

Description

FEATURES

- New Light Design, simple and fashioned design with 4 different color for body (optional)
- Die-casting aluminum housing
- Weather resistance surface, enhanced with anti-corrosive treatments
- One button press to open housing for easy maintenance
- CREE LEDs (upcoming model)
- Highest Quality
- Highest Lumious 110 to 130 lm/W

	SSL2-30	SSL2-40	SSL2-60	SSL2-90	SSL2-110	SSL2-130
L2D Quantity	50 pcs	50 pcs	50 pcs	50 pcs	50 pcs	50 pcs
Rated Power	30 W	40 W	60 W	90 W	110 W	130 W
Input Voltage	100-277 VAC	100-277 VAC	100-277 VAC	100-277 VAC	100-277 VAC	100-277 VAC
Frequency Range	50/60 Hz	50/60 Hz	50/60 Hz	50/60 Hz	50/60 Hz	50/60 Hz
Type	<120°	<120°	<120°	<120°	<120°	<120°
Color	6000K/4000K/3000K	6000K/4000K/3000K	6000K/4000K/3000K	6000K/4000K/3000K	6000K/4000K/3000K	6000K/4000K/3000K
Beam Spread (mrad)	<120°/120°	<120°/120°	<120°/120°	<120°/120°	<120°/120°	<120°/120°
Beam Spread (mrad)	60°/60°	60°/60°	60°/60°	60°/60°	60°/60°	60°/60°
Lamp Luminaire Flux (lm)	220lm/220lm/110lm	320lm/320lm/160lm	530lm/530lm/265lm	780lm/780lm/390lm	980lm/980lm/490lm	1180lm/1180lm/590lm
Range of Working Condition	-20° to 50°	-20° to 50°	-20° to 50°	-20° to 50°	-20° to 50°	-20° to 50°
Heat of Working Condition	10% to 90%	10% to 90%	10% to 90%	10% to 90%	10% to 90%	10% to 90%
Life span	>50,000 hours	>50,000 hours	>50,000 hours	>50,000 hours	>50,000 hours	>50,000 hours
Warranty	3 years	3 years	3 years	3 years	3 years	3 years
Protection Grade	IP65	IP65	IP65	IP65	IP65	IP65
IK Grade	IK10	IK10	IK10	IK10	IK10	IK10
Installation Pipe Diameter	ø48mm/ø48mm	ø48mm/ø48mm	ø48mm/ø48mm	ø48mm/ø48mm	ø48mm/ø48mm	ø48mm/ø48mm
Installation Height	4.5m	5.5m	6.5m	8.5m	9.5m	10.5m
Lamp Height (mm)	1.5	1.5	1.5	1.5	1.5	1.5
Cable Packing Size	75mm x 30 pin x 180mm	75mm x 30 pin x 180mm	75mm x 30 pin x 180mm	80mm x 40 pin x 240mm	80mm x 40 pin x 240mm	80mm x 40 pin x 240mm
Cable Weight (kg)	7	7	7	13	13	13
Certificate	CE/RoHS	CE/RoHS	CE/RoHS	CE/RoHS	CE/RoHS	CE/RoHS