

SSL3-60



Street Light 60W

Rating: Not Rated Yet
[Ask a question about this product](#)

Description

FEATURES

- Use Vapor Chamber to solve the heat problem of high power LEDs.
- Ultra-low thermal resistance welding technology between LED Module and VC.
- Up to 94% light transmission.
- Rectangular facula with 15°adjustable.
- Application: Suitable for street, square, park and industrial area etc.

SPECIFICATION

	SSL3-30	SSL3-45	SSL3-60	SSL3-90	SSL3-120
Power	30Watts	45Watts	60Watts	90Watts	120Watts
LED	CREE	CREE	CREE	CREE	CREE
Input voltage	AC85V ~ AC255V or DC12~DC24V	AC100V ~ AC264V or DC12~DC24V	AC100V ~ AC264V or DC12~DC24V	AC100V ~ AC264V or DC12~DC24V	AC100V ~ AC264V or DC12~DC24V
Current	300mA	450mA	600mA	900mA	1200mA
Frequency Range	50~60Hz	50~60Hz	50~60Hz	50~60Hz	50~60Hz
Power Factor	>0.9	>0.9	>0.9	>0.9	>0.9
Colour Temperature	2700K ~ 7000K	2700K ~ 7000K	2700K ~ 7000K	2700K ~ 7000K	2700K ~ 7000K
Colour Rendering Index	>85	>85	>85	>85	>85
Lamp Luminous Flux	1650-2550 lm	2560-3825 lm	3560-7650 lm	5850-7650 lm	8775-11475 lm
Lamp Efficiency	>80%	>80%	>80%	>80%	>80%
Temperature of Working Condition	-30°C-50°C	-30°C-50°C	-30°C-50°C	-30°C-50°C	-30°C-50°C
Beam Angle	90° and 135°	90° and 135°	90° and 135°	90° and 135°	90° and 135°
Warranty period	3 Years	3 Years	3 Years	3 Years	3 Years
Protection Grade	IP65	IP65	IP65	IP65	IP65
Net Weight	4.3Kg	4.5Kg	5.5Kg	7Kg	10Kg
Packing Size	52mmx21mmx16cm	52mmx21mmx16cm	63mmx26mmx16cm	75mmx26mmx23cm	86mmx36mmx23cm