SSI-SB



SMART LED Obstruction Light 6W

Rating: Not Rated Yet
Ask a question about this product

Description

| | SSI-SA | SSI-SB |
|---------------------|---|---|
| | | |
| Light Source | 2x3 Luxeon LED or 24pcs Ultra Bright LED | 2x3 Luxeon LED or 24pcs Ultra Bright LED |
| Light intensity | > 10 Cd | > 10 Cd |
| Power supply | 100-240VAC or 12VDC | 100-240VAC or 12VDC |
| Power consumption | < 6W | < 6W |
| Colour | Aviation Red | Aviation Red |
| Lens | Medium intensity glass 5mm thickness | Medium intensity glass 5mm thickness |
| Housing | Aluminium alloy | Aluminium alloy |
| Protection | IP65 | IP65 |
| Light mode | Fixed or flashing | Fixed or flashing |
| Working temperature | -20°C to 60°C | -20°C to 60°C |
| Dimension | Height: 180mm | Height: 180mm |
| | Φ: 70mm | Ф : 130mm |
| Weight | 1kg | 1.5kg |
| Warranty | 2 years for LED, 1 year for parts | 2 years for LED, 1 year for parts |
| Optional | Solar System Kit to protect BTS Mains Distribution Panel from lightning induction current | Solar System Kit to protect BTS Mains Distribution Panel from lightning induction current |